

Global Design Solutions



www.gds.uk.com

## LiteWare UL


40w RGB Battery Uplighter  
with Wireless DMX

Introducing the new

## LiteWare HO

80w High Output  
RGB Battery Uplighter  
with Wireless DMX

Now you can get  
more light anywhere.



Nelson's Column, London,  
using 1x LiteWare HO



Victoria & Albert Museum, London,  
using 9x LiteWare UL

# LiteWare UL

## 40w RGB Battery Uplighter with Wireless DMX

**LiteWare UL** – the original LiteWare RGB Uplighter outputting 40watts of wireless RGB light with a reliable battery energy source, encased in a stainless steel housing, reflecting its own surroundings using Wireless DMX.

### Features

- 40W RGB LED emitter
- Wireless DMX Control
- Automatic deployable Aerial
- 24 hour runtime from fully charged battery (14 hours on full white)
- IP45 - interior/ exterior use
- 50 preset colours Lee & Rosco matched
- 20 preset snaps/fades
- Charging cycle 6 hours
- Available singularly or in Flightcases with inbuilt charging
- Finished in stainless steel to blend in with any surrounding
- Mapped dimming curve for smooth transitions
- Kensington Security lock ready



# LiteWare HO

## 80w High Output RGB Battery Uplighter with Wireless DMX

**LiteWare HO** – the new High Output LiteWare RGB Uplighter outputting 80watts of wireless RGB light, using all the proven technology used in the successful LiteWare UL, both fittings are fully compatible with all accessories in either range.

### Features

- 80W RGB LED emitter
- Wireless DMX Control
- Automatic deployable Aerial
- 12 hour runtime from fully charged battery (7 hours on full white)
- IP45 - interior/ exterior use
- 50 preset colours Lee & Rosco matched
- 20 preset snaps/fades
- Charging cycle 6 hours
- Available singularly or in Flightcases with inbuilt charging
- Finished in stainless steel to blend in with any surrounding
- Mapped dimming curve for smooth transitions
- Kensington Security lock ready



## LiteWare 6Way Charging Flightcase

The LiteWare 6 way flightcase provides the charging station, storage and transportation for LiteWare. All the charging is built into the secure base of the case with an external inlet for mains power. The LiteWare units simply drop into the secure foam slots and automatically locate onto the charger. Once the units are located they automatically turn off and unlink any wireless DMX connection.

The charging system will work anywhere in the world on an 80V – 240V supply, charging the units from flat in 6 – 8hours. An indication is provided on the unit to ascertain charging/charged status. Once the units are charged and disconnected from the external supply they will remain fully charged for six months.



## LiteWare Floor Stand

The Floor stand allows you to now orient any LiteWare fitting for more flexibility. With a robust design and securely fastening the unit to it, LiteWare floor stand provides a 90degree vertical adjustment.




## LiteWare Sleeves

LiteWare sleeves are an option allowing the colour of the unit to be altered if required, simply sliding over the unit. Any RAL colour option is available.

## LiteWare RGB Battery Uplighter dimensions

### LiteWare UL

weight 15kgs (33 lbs)



top view

172 mm



side view


179 mm



front view

### LiteWare OL

weight 15kgs (33 lbs)



top view

**For further information please contact:**

Global Design Solutions  
176 Brynland Avenue,  
Bristol BS7 9DY UK.

Tel: +44 (0117) 325 0063  
Fax: +44 (0117) 924 5515

[salesuk@gds.uk.com](mailto:salesuk@gds.uk.com)  
[www.gds.uk.com](http://www.gds.uk.com)

Global Design Solutions  
789 Blvd East, Weehawken,  
NJ 07086 USA.

Tel: +1 (201) 824 5082  
Fax: +1 (201) 425 7299

[salesus@gds.uk.com](mailto:salesus@gds.uk.com)  
[www.gds.uk.com](http://www.gds.uk.com)

Global Design Solutions



[www.gds.uk.com](http://www.gds.uk.com)